



Fiber Optic Cables

MLT-DGSTA-DJ-(AY50)

A-DF(ZN)2Y2B2Y

Multi loose tube, double galvanized steel tape armor fiber optic cable.

RoHS REACH CE



Application

- . Suitable for pushing, blowing method.
- . In heavy duty environments.
- . As a backbone cable in telecommunication lines.
- . Rodent protection.
- . Extra strength due to double layer of galvanized steel.

Cable Construction

- 1 - Optical fiber core ¹
- 2 - Waterproof thixotropic jelly
- 3 - PBT Tube
- 4 - Non-metallic central strength member (FRP)
- 5- Jelly filling
- 6 - Core Wrapping (Polyester Tape)
- 7 - Non-metallic strength member (Aramid yarn)
- 8 - Ripcord
- 9 - UV resistant polyethylene (LLDPE) black inner jacket
- 10 - Water-swellable tape
- 11 - Two helically laid galvanized steel tape
- 12 - Ripcord
- 13 - UV resistant polyethylene (HDPE) black outer jacket

Mechanical and Environmental Characteristics

	Test Standard	Specified Value	Acceptance Criteria
Maximum Installation Tension ²	IEC 60794-1-2-E1	3.0 x W(N), min. 5000 N	Fiber strain ≤ 0.33%
Maximum Operation Tension	IEC 60794-1-2-E1	1.0 x W(N), min. 1500 N	Δα ≤ 0.05 dB, No fiber strain
Crush Strength	IEC 60794-1-2-E3	4000 N / 100 mm, max. 15 min.	Δα ≤ 0.05 dB, No damage
Impact	IEC 60794-1-2-E4	10 Nm, 3 impacts, R= 300 mm	Δα ≤ 0.05 dB after the test
Torsion	IEC 60794-1-2-E7	1 m. 100N, +/- 180°, 10 cycles	Δα ≤ 0.05 dB, No damage
Repeated Bending	IEC 60794-1-2-E6	R=20x D, 100 N, 35 cycles	No damage
Bending Radius	IEC 60794-1-2-E11	R=20x D, 4 turns, 3 cycles	Δα ≤ 0.05 dB, No damage
Temperature Cycling	IEC 60794-1-2-F1	-20°C to +70°C	Δα ≤ 0.05 dB/km
Waterproofness	IEC 60794-1-2-F5B	Sample= 3 m, water column= 1 m	No water leakage in 24 hours.

Application

	Minimum Bending Radius		Temperature Range	
Operation	20 x cable Ø	Storage	-40°C to +70°C	Installation -30 to +60°C
Fixed	15 x cable Ø	Transport	-40°C to +70°C	Operating -20°C to +70°C

Marking, Packing, Delivery Lengths

Marking	ETK Kablo <Date of Manufacture> <Fiber Count and Type> <Length Marking>
Packing	Wooden drum with protection
Delivery Lengths	2 km, 4 km ± %5 tolerance

Notes

¹ Optical fiber core could be applied as G.652.D, G.655, G.657.A1, G.657.A2, OM1, OM2, OM3, OM4 according to customer demand.

² Maximum tensile strength could be changed according to customer demand.

Manufacturing Standard: TS EN 60794-3-12

MLT-DGSTA-DJ-(AY50)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.245.2.6.1.0900.0.0002	SM G.652.D	2	1	5	2.05	2.2	17.3	369
3.245.2.6.1.0900.1.0004	SM G.652.D	4	1	5	2.05	2.2	17.3	368
3.245.2.6.1.0900.0.0004	SM G.652.D	4	2	4	2.05	2.2	17.3	369
3.245.2.6.1.0900.1.0006	SM G.652.D	6	1	5	2.05	2.2	17.3	368
3.245.2.6.1.0900.0.0006	SM G.652.D	6	3	3	2.05	2.2	17.3	370
3.245.2.6.1.0900.1.0008	SM G.652.D	8	1	5	2.05	2.2	17.3	368
3.245.2.6.1.0900.2.0008	SM G.652.D	8	2	4	2.05	2.2	17.3	369
3.245.2.6.1.0900.0.0008	SM G.652.D	8	4	2	2.05	2.2	17.3	371
3.245.2.6.1.0900.1.0012	SM G.652.D	12	1	5	2.25	2.2	17.7	386
3.245.2.6.1.0900.2.0012	SM G.652.D	12	3	3	2.05	2.2	17.3	370
3.245.2.6.1.0900.0.0012	SM G.652.D	12	6	0	2.05	2.2	17.3	372
3.245.2.6.1.0900.1.0016	SM G.652.D	16	2	4	2.05	2.2	17.3	369
3.245.2.6.1.0900.0.0016	SM G.652.D	16	4	2	2.05	2.2	17.3	370
3.245.2.6.1.0900.0.0020	SM G.652.D	20	5	1	2.05	2.2	17.3	371
3.245.2.6.1.0900.1.0024	SM G.652.D	24	2	4	2.25	2.2	17.7	384
3.245.2.6.1.0900.3.0024	SM G.652.D	24	3	3	2.05	2.2	17.3	369
3.245.2.6.1.0900.2.0024	SM G.652.D	24	4	2	2.05	2.2	17.3	370
3.245.2.6.1.0900.0.0024	SM G.652.D	24	6	0	2.05	2.2	17.3	371
3.245.2.6.1.0900.0.0032	SM G.652.D	32	4	2	2.05	2.2	17.3	369
3.245.2.6.1.0900.1.0036	SM G.652.D	36	3	3	2.25	2.2	17.7	384
3.245.2.6.1.0900.0.0036	SM G.652.D	36	6	0	2.05	2.2	17.3	371
3.245.2.6.1.0900.1.0048	SM G.652.D	48	4	2	2.25	2.2	18.0	609
3.245.2.6.1.0900.0.0048	SM G.652.D	48	6	0	2.05	2.2	17.3	370
3.245.2.6.1.0900.0.0060	SM G.652.D	60	5	1	2.25	2.5	18.0	399
3.245.2.6.1.0900.0.0064	SM G.652.D	64	8	0	2.05	2.7	19.0	440
3.245.2.6.1.0900.0.0072	SM G.652.D	72	6	0	2.25	2.5	18.0	399
3.245.2.6.1.0900.0.0096	SM G.652.D	96	8	0	2.25	2.7	19.4	457
3.245.2.6.1.0900.0.0144	SM G.652.D	144	12	0	2.25	2.7	22.4	588