



Fiber Optic Cables

MLT-SA-SJ-A(S)-(GY27)

A-DF(ZN)(SR)T2Y

Multi loose tube, non-metallic armor, aerial fiber optic cable.

RoHS REACH CE



Application

- Fast and easy application due to its light construction.
- For aerial applications.
- In heavy duty environments.
- Suitable to be used up to 40 meters pole span.
- As a backbone cable in telecommunication lines.

Cable Construction

- 1 - Optical fiber core ¹
- 2 - Waterproof thixotropic jelly
- 3 - PBT Tube
- 4 - Non-metallic central strength member (FRP)
- 5 - Jelly filling
- 6 - Core Wrapping (Polyester Tape)
- 7 - Non-metallic strength member (Glass yarn)
- 8 - Ripcord
- 9 - Corrugated steel tape
- 10 - Web
- 11 - Steel messenger wire (7x1.12 mm)
- 12- UV resistant polyethylene (HDPE) black outer jacket

Mechanical and Environmental Characteristics

	Test Standard	Specified Value	Acceptance Criteria
Maximum Installation Tension ²	IEC 60794-1-2-E1	1.5 x W(N), min. 2700 N	Fiber strain ≤ 0.33%
Maximum Operation Tension	IEC 60794-1-2-E1	0.5 x W(N), min. 900 N	Δα ≤ 0.05 dB, No fiber strain
Crush Strength	IEC 60794-1-2-E3	3000 N / 100 mm, max. 15 min.	Δα ≤ 0.05 dB, No damage
Impact	IEC 60794-1-2-E4	10 Nm, 3 impacts, R= 300 mm	Δα ≤ 0.05 dB after the test
Torsion	IEC 60794-1-2-E7	1 m. 100N, +/- 180°, 10 cycles	Δα ≤ 0.05 dB, No damage
Repeated Bending	IEC 60794-1-2-E6	R=20x D, 100 N, 35 cycles	No damage
Bending Radius	IEC 60794-1-2-E11	R=20x D, 4 turns, 3 cycles	Δα ≤ 0.05 dB, No damage
Temperature Cycling	IEC 60794-1-2-F1	-20°C to +70°C	Δα ≤ 0.05 dB/km
Waterproofness	IEC 60794-1-2-F5B	Sample= 3 m, water column= 1 m	No water leakage in 24 hours.

Application

	Minimum Bending Radius		Temperature Range		
Operation	20 x cable Ø	Storage	-40°C to +70°C	Installation	-30 to +60°C
Fixed	15 x cable Ø	Transport	-40°C to +70°C	Operating	-40°C to +70°C

Marking, Packing, Delivery Lengths

Marking	ETK Kablo <Date of Manufacture> <Fiber Count and Type> <Length Marking>
Packing	Wooden drum with protection
Delivery Lengths	2 km, 4 km ± %5 tolerance

Notes

¹ Optical fiber core could be applied as G.652.D, G.655, G.657.A1, G.657.A2, OM1, OM2, OM3, OM4 according to customer demand.

² Maximum tensile strength could be changed according to customer demand.

Manufacturing Standard: TS EN 60794-3-12

MLT-SA-SJ-A(S)-(GY27)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.233.0.6.1.0900.0.0002	SM G.652.D	2	1	5	2.05	2.2	11.5	233
3.233.0.6.1.0900.1.0004	SM G.652.D	4	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0900.0.0004	SM G.652.D	4	2	4	2.05	2.2	11.5	237
3.233.0.6.1.0900.1.0006	SM G.652.D	6	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0900.0.0006	SM G.652.D	6	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0900.1.0008	SM G.652.D	8	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0900.2.0008	SM G.652.D	8	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0900.0.0008	SM G.652.D	8	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0900.1.0012	SM G.652.D	12	1	5	2.25	2.2	11.6	236
3.233.0.6.1.0900.2.0012	SM G.652.D	12	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0900.0.0012	SM G.652.D	12	6	0	2.05	2.2	11.5	238
3.233.0.6.1.0900.1.0016	SM G.652.D	16	2	4	2.05	2.2	11.5	234
3.233.0.6.1.0900.0.0016	SM G.652.D	16	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0900.0.0020	SM G.652.D	20	5	1	2.05	2.2	11.5	236
3.233.0.6.1.0900.1.0024	SM G.652.D	24	2	4	2.25	2.2	11.6	236
3.233.0.6.1.0900.3.0024	SM G.652.D	24	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0900.2.0024	SM G.652.D	24	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0900.0.0024	SM G.652.D	24	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0900.0.0032	SM G.652.D	32	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0900.1.0036	SM G.652.D	36	3	3	2.25	2.2	11.6	237
3.233.0.6.1.0900.0.0036	SM G.652.D	36	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0900.1.0048	SM G.652.D	48	4	2	2.25	2.2	12.2	252
3.233.0.6.1.0900.0.0048	SM G.652.D	48	6	0	2.05	2.2	11.5	236
3.233.0.6.1.0900.0.0060	SM G.652.D	60	5	1	2.25	2.5	12.4	259
3.233.0.6.1.0900.0.0064	SM G.652.D	64	8	0	2.05	2.2	13.4	310
3.233.0.6.1.0900.0.0072	SM G.652.D	72	6	0	2.25	2.5	12.4	259
3.233.0.6.1.0900.0.0096	SM G.652.D	96	8	0	2.25	2.7	13.8	317

MLT-SA-SJ-A(S)-(GY27)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.233.0.6.1.0625.0.0002	OM1	2	1	5	2.05	2.2	11.5	233
3.233.0.6.1.0625.1.0004	OM1	4	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0625.0.0004	OM1	4	2	4	2.05	2.2	11.5	237
3.233.0.6.1.0625.1.0006	OM1	6	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0625.0.0006	OM1	6	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0625.1.0008	OM1	8	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0625.2.0008	OM1	8	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0625.0.0008	OM1	8	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0625.1.0012	OM1	12	1	5	2.25	2.2	11.6	236
3.233.0.6.1.0625.2.0012	OM1	12	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0625.0.0012	OM1	12	6	0	2.05	2.2	11.5	238
3.233.0.6.1.0625.1.0016	OM1	16	2	4	2.05	2.2	11.5	234
3.233.0.6.1.0625.0.0016	OM1	16	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0625.0.0020	OM1	20	5	1	2.05	2.2	11.5	236
3.233.0.6.1.0625.1.0024	OM1	24	2	4	2.25	2.2	11.6	236
3.233.0.6.1.0625.3.0024	OM1	24	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0625.2.0024	OM1	24	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0625.0.0024	OM1	24	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0625.0.0032	OM1	32	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0625.1.0036	OM1	36	3	3	2.25	2.2	11.6	237
3.233.0.6.1.0625.0.0036	OM1	36	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0625.1.0048	OM1	48	4	2	2.25	2.2	12.2	252
3.233.0.6.1.0625.0.0048	OM1	48	6	0	2.05	2.2	11.5	236
3.233.0.6.1.0625.0.0060	OM1	60	5	1	2.25	2.5	12.4	259
3.233.0.6.1.0625.0.0064	OM1	64	8	0	2.05	2.2	13.4	310
3.233.0.6.1.0625.0.0072	OM1	72	6	0	2.25	2.5	12.4	259
3.233.0.6.1.0625.0.0096	OM1	96	8	0	2.25	2.7	13.8	319

MLT-SA-SJ-A(S)-(GY27)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.233.0.6.1.0502.0.0002	OM2	2	1	5	2.05	2.2	11.5	233
3.233.0.6.1.0502.1.0004	OM2	4	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0502.0.0004	OM2	4	2	4	2.05	2.2	11.5	237
3.233.0.6.1.0502.1.0006	OM2	6	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0502.0.0006	OM2	6	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0502.1.0008	OM2	8	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0502.2.0008	OM2	8	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0502.0.0008	OM2	8	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0502.1.0012	OM2	12	1	5	2.25	2.2	11.6	236
3.233.0.6.1.0502.2.0012	OM2	12	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0502.0.0012	OM2	12	6	0	2.05	2.2	11.5	238
3.233.0.6.1.0502.1.0016	OM2	16	2	4	2.05	2.2	11.5	234
3.233.0.6.1.0502.0.0016	OM2	16	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0502.0.0020	OM2	20	5	1	2.05	2.2	11.5	236
3.233.0.6.1.0502.1.0024	OM2	24	2	4	2.25	2.2	11.6	236
3.233.0.6.1.0502.3.0024	OM2	24	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0502.2.0024	OM2	24	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0502.0.0024	OM2	24	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0502.0.0032	OM2	32	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0502.1.0036	OM2	36	3	3	2.25	2.2	11.6	237
3.233.0.6.1.0502.0.0036	OM2	36	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0502.1.0048	OM2	48	4	2	2.25	2.2	12.2	252
3.233.0.6.1.0502.0.0048	OM2	48	6	0	2.05	2.2	11.5	236
3.233.0.6.1.0502.0.0060	OM2	60	5	1	2.25	2.5	12.4	259
3.233.0.6.1.0502.0.0064	OM2	64	8	0	2.05	2.2	13.4	310
3.233.0.6.1.0502.0.0072	OM2	72	6	0	2.25	2.5	12.4	259
3.233.0.6.1.0502.0.0096	OM2	96	8	0	2.25	2.7	13.8	319

MLT-SA-SJ-A(S)-(GY27)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.233.0.6.1.0503.0.0002	OM3	2	1	5	2.05	2.2	11.5	233
3.233.0.6.1.0503.1.0004	OM3	4	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0503.0.0004	OM3	4	2	4	2.05	2.2	11.5	237
3.233.0.6.1.0503.1.0006	OM3	6	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0503.0.0006	OM3	6	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0503.1.0008	OM3	8	1	5	2.05	2.2	11.5	234
3.233.0.6.1.0503.2.0008	OM3	8	2	4	2.05	2.2	11.5	235
3.233.0.6.1.0503.0.0008	OM3	8	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0503.1.0012	OM3	12	1	5	2.25	2.2	11.6	236
3.233.0.6.1.0503.2.0012	OM3	12	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0503.0.0012	OM3	12	6	0	2.05	2.2	11.5	238
3.233.0.6.1.0503.1.0016	OM3	16	2	4	2.05	2.2	11.5	234
3.233.0.6.1.0503.0.0016	OM3	16	4	2	2.05	2.2	11.5	236
3.233.0.6.1.0503.0.0020	OM3	20	5	1	2.05	2.2	11.5	236
3.233.0.6.1.0503.1.0024	OM3	24	2	4	2.25	2.2	11.6	236
3.233.0.6.1.0503.3.0024	OM3	24	3	3	2.05	2.2	11.5	235
3.233.0.6.1.0503.2.0024	OM3	24	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0503.0.0024	OM3	24	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0503.0.0032	OM3	32	4	2	2.05	2.2	11.5	235
3.233.0.6.1.0503.1.0036	OM3	36	3	3	2.25	2.2	11.6	237
3.233.0.6.1.0503.0.0036	OM3	36	6	0	2.05	2.2	11.5	237
3.233.0.6.1.0503.1.0048	OM3	48	4	2	2.25	2.2	12.2	252
3.233.0.6.1.0503.0.0048	OM3	48	6	0	2.05	2.2	11.5	236
3.233.0.6.1.0503.0.0060	OM3	60	5	1	2.25	2.5	12.4	259
3.233.0.6.1.0503.0.0064	OM3	64	8	0	2.05	2.2	13.4	310
3.233.0.6.1.0503.0.0072	OM3	72	6	0	2.25	2.5	12.4	259
3.233.0.6.1.0503.0.0096	OM3	96	8	0	2.25	2.7	13.8	319