

Data/LAN Cables

Cat 6 SF/UTP PVC



Application Cable Construction

- | | | | | | | | | | | | | | | | | | | | |
|---|--|--|---|-------------------------------------|----------------|---|-------------------------------|---------------|---|-------------------------------------|---------------|---|--|------------|---|---|------------------|---|--|
| <ul style="list-style-type: none"> • ISDN • 4/6 Mbps Token Ring (IEEE 802.5) • 100 Mbps CDDI • 250 Mbps ATM Power over Ethernet (PoE) • 10 BASE-T Ethernet (IEEE 802.3j) • 100 BASE-VG AnyLAN (IEEE 802.12) • 1000 BASE-T 1 Gigabit Ethernet (IEEE 802.3 ab) | <table border="0"> <tr><td>1 - Conductor</td><td>:</td><td>Electrolytic solid copper conductor</td></tr> <tr><td>2 - Insulation</td><td>:</td><td>Solid polyethylene insulation</td></tr> <tr><td>3 - Stranding</td><td>:</td><td>Insulations are stranded into pairs</td></tr> <tr><td>4 - Separator</td><td>:</td><td>Pairs are stranded together with star shaped separator</td></tr> <tr><td>5 - Screen</td><td>:</td><td>Drain wire, Al/PET tape, tinned copper braiding</td></tr> <tr><td>6 - Outer Jacket</td><td>:</td><td>UV resistant PVC outer jacket, RAL 7035 (Grey)</td></tr> </table> | 1 - Conductor | : | Electrolytic solid copper conductor | 2 - Insulation | : | Solid polyethylene insulation | 3 - Stranding | : | Insulations are stranded into pairs | 4 - Separator | : | Pairs are stranded together with star shaped separator | 5 - Screen | : | Drain wire, Al/PET tape, tinned copper braiding | 6 - Outer Jacket | : | UV resistant PVC outer jacket, RAL 7035 (Grey) |
| 1 - Conductor | : | Electrolytic solid copper conductor | | | | | | | | | | | | | | | | | |
| 2 - Insulation | : | Solid polyethylene insulation | | | | | | | | | | | | | | | | | |
| 3 - Stranding | : | Insulations are stranded into pairs | | | | | | | | | | | | | | | | | |
| 4 - Separator | : | Pairs are stranded together with star shaped separator | | | | | | | | | | | | | | | | | |
| 5 - Screen | : | Drain wire, Al/PET tape, tinned copper braiding | | | | | | | | | | | | | | | | | |
| 6 - Outer Jacket | : | UV resistant PVC outer jacket, RAL 7035 (Grey) | | | | | | | | | | | | | | | | | |

Technical Characteristics

Conductor Resistance Ω /km (20 °C)	Insulation Resistance M Ω /km (20 °C)	Mutual Capacitance nF/km	Resistance Unbalance %	Propagation Velocity %	Characteristic Impedance Ω (1-250 MHz)	Operating Voltage V DC	Test Voltage V (DC. 1 minute)
Max. 94	5000	Max. 56	%2	%67-69	100 \pm %15	250	1200

Mechanical Characteristics

Bending Radius	Temperature Range Operating
8.0xD mm	-20°C ~ +60°C

Standards

Manufacturing	Flame Retardancy Test
ANSI/TIA-568-C.2, IEC-61156-5, IEC-11801	IEC 60332-1-2, VDE 0482-332-1-2, EN 60332-1-2

Electrical Properties

Frequency MHz	Insertion Loss dB/100m (Max.)	Near-end Crosstalk (NEXT) dB (Min.)	Power-sum Near-end Crosstalk (PSNEXT) dB (Min.)	Equal-level Far-end Crosstalk (ELFEXT) dB/100m (Min.)	Power-sum Equal Level Far-end Crosstalk (PSELFEXT) dB/100m (Min.)	Return Loss (RL) dB (Min.)
1	2	74.3	72.3	67.8	64.8	20
4	3.8	65.3	63.3	55.8	52.8	23
8	5.3	60.8	58.8	49.7	46.7	24.5
10	6	59.3	57.3	47.8	44.8	25
16	7.6	56.2	54.2	43.7	40.7	25
20	8.5	54.8	52.8	41.8	38.8	24.3
25	9.5	53.3	51.3	39.8	36.8	23.6
31.25	10.7	51.9	49.9	37.9	34.9	21.5
62.5	15.4	47.4	45.4	31.9	28.9	20.1
100	19.8	44.3	42.3	27.8	24.8	18
200	29	39.8	37.8	21.8	18.8	17.3
250	32.8	38.3	36.3	19.8	16.8	16.8

Cat 6 SF/UTP PVC

Part Number	Pair Count	Conductor Diameter (AWG)	Approx. Cable Diameter (mm)	Copper Weight (kg/km)	Approx. Weight (kg/km)	Packing Lengths (m)
3.446.2.1.2.0057.0.0004	4	23	7.2	25.6	58	500/1000