



Fiber Optic Cables

MLT-NMA-DJ-(GY27)-(D)

RoHS REACH CE

A-DQ2Y(ZN)2Y

Multi loose tube, non-metallic armor fiber optic cable.



Application

- Fast and easy application due to its light construction.
- Direct burial and duct type applications.
- Suitable for pushing, blowing method.
- Problem-free use in power lines due to its non-metallic construction.
- In MAN, WAN, LAN applications or as a backbone cable for GSM, CATV, SMATV networks.
- Rodent protection.

Cable Construction

- 1 - Optical fiber core ¹
- 2 - Waterproof thixotropic jelly
- 3 - PBT Tube
- 4 - Non-metallic central strength member (FRP)
- 5 - Water-swellaable yarn
- 6 - Core Wrapping (Water-swellaable Tape)
- 7 - Ripcord
- 8 - UV resistant polyethylene (LLDPE) black inner jacket.
- 9 - Non-metallic strength member (Glass yarn)
- 10- Ripcord
- 11- UV resistant polyethylene (HDPE) black outer jacket

Mechanical and Environmental Characteristics

	Test Standard	Specified Value	Acceptance Criteria
Maximum Installation Tension ²	IEC 60794-1-2-E1	1.5 x W(N), min. 2700 N	Fiber strain ≤ 0.33%
Maximum Operation Tension	IEC 60794-1-2-E1	0.5 x W(N), min. 900 N	Δa ≤ 0.05 dB, No fiber strain
Crush Strength	IEC 60794-1-2-E3	4000 N / 100 mm, max. 15 min.	Δa ≤ 0.05 dB, No damage
Impact	IEC 60794-1-2-E4	10 Nm, 3 impacts, R= 300 mm	Δa ≤ 0.05 dB after the test
Torsion	IEC 60794-1-2-E7	1 m. 100N, +/- 180°, 10 cycles	Δa ≤ 0.05 dB, No damage
Repeated Bending	IEC 60794-1-2-E6	R=20x D, 100 N, 35 cycles	No damage
Bending Radius	IEC 60794-1-2-E11	R=20x D, 4 turns, 3 cycles	Δa ≤ 0.05 dB, No damage
Temperature Cycling	IEC 60794-1-2-F1	-20°C to +70°C	Δa ≤ 0.05 dB/km
Waterproofness	IEC 60794-1-2-F5B	Sample= 3 m, water column= 1 m	No water leakage in 24 hours.

Application

	Minimum Bending Radius		Temperature Range		
Operation	20 x cable Ø	Storage	-40 to +70°C	Installation	-30 to +60°C
Fixed	15 x cable Ø	Transport	-40 to +70°C	Operating	-40°C to +70°C

Marking, Packing, Delivery Lengths

Marking	ETK Kablo <Date of Manufacture> <Fiber Count and Type> <Length Marking>
Packing	Wooden drum with protection
Delivery Lengths	2 km, 4 km ± %5 tolerance

Notes

¹ Optical fiber core could be applied as G.652.D, G.655, G.657.A1, G.657.A2, OM1, OM2, OM3, OM4 according to customer demand.

² Maximum tensile strength could be changed according to customer demand.

Manufacturing Standard: TS EN 60794-3-12

MLT-NMA-DJ-(GY27)-(D)

Part Number	Core Type	Fiber Count	Tube Count	Filler Count	Tube Diameter (mm)	FRP Diameter (mm)	Cable Diameter (mm)	Cable Weight (kg/km)
3.243.2.6.1.0900.0.1002	SM G.652.D	2	1	5	2.05	2.2	12.5	124
3.243.2.6.1.0900.1.1004	SM G.652.D	4	1	5	2.05	2.2	12.5	124
3.243.2.6.1.0900.0.1004	SM G.652.D	4	2	4	2.05	2.2	12.5	125
3.243.2.6.1.0900.1.1006	SM G.652.D	6	1	5	2.05	2.2	12.5	124
3.243.2.6.1.0900.0.1006	SM G.652.D	6	3	3	2.05	2.2	12.5	125
3.243.2.6.1.0900.1.1008	SM G.652.D	8	1	5	2.05	2.2	12.5	124
3.243.2.6.1.0900.2.1008	SM G.652.D	8	2	4	2.05	2.2	12.5	125
3.243.2.6.1.0900.0.1008	SM G.652.D	8	4	2	2.05	2.2	12.5	126
3.243.2.6.1.0900.1.1012	SM G.652.D	12	1	5	2.25	2.5	13.2	136
3.243.2.6.1.0900.2.1012	SM G.652.D	12	3	3	2.05	2.2	12.5	125
3.243.2.6.1.0900.0.1012	SM G.652.D	12	6	0	2.05	2.2	12.5	128
3.243.2.6.1.0900.1.1016	SM G.652.D	16	2	4	2.05	2.2	12.5	124
3.243.2.6.1.0900.0.1016	SM G.652.D	16	4	2	2.05	2.2	12.5	126
3.243.2.6.1.0900.0.1020	SM G.652.D	20	5	1	2.05	2.2	12.5	126
3.243.2.6.1.0900.1.1024	SM G.652.D	24	2	4	2.25	2.5	13.2	137
3.243.2.6.1.0900.3.1024	SM G.652.D	24	3	3	2.05	2.2	12.5	125
3.243.2.6.1.0900.2.1024	SM G.652.D	24	4	2	2.05	2.2	12.5	125
3.243.2.6.1.0900.0.1024	SM G.652.D	24	6	0	2.05	2.2	12.5	127
3.243.2.6.1.0900.0.1032	SM G.652.D	32	4	2	2.05	2.2	12.6	125
3.243.2.6.1.0900.0.1036	SM G.652.D	36	3	3	2.25	2.5	14.2	156
3.243.2.6.1.0900.1.1036	SM G.652.D	36	6	0	2.05	2.2	12.5	126
3.243.2.6.1.0900.1.1048	SM G.652.D	48	4	2	2.25	2.5	13.2	137
3.243.2.6.1.0900.0.1048	SM G.652.D	48	6	0	2.05	2.2	12.6	128
3.243.2.6.1.0900.0.1060	SM G.652.D	60	5	1	2.25	2.5	13.2	137
3.243.2.6.1.0900.0.1064	SM G.652.D	64	8	0	2.05	2.7	14.2	157
3.243.2.6.1.0900.0.1072	SM G.652.D	72	6	0	2.25	2.5	14.2	157
3.243.2.6.1.0900.0.1096	SM G.652.D	96	8	0	2.25	2.7	17.6	190
3.243.2.6.1.0900.0.1120	SM G.652.D	120	10	0	2.25	2.7	17.6	209
3.243.2.6.1.0900.0.1144	SM G.652.D	144	12	0	2.25	2.7	18.5	259