

## **CERTIFICATE OF CONSTANCY OF PERFORMANCE**

**3130-CPR-020**

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Cable type : CAT 6 / 6A U / FTP**

**Reaction to fire class : B2<sub>ca</sub>-s1a, d1, a1**

*Cables used in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke*

placed on the market under the name or trade mark of

**ETK KABLO SANAYİ VE TİCARET A.Ş.**

**OSMANGAZİ MAH. MÜSTESNA SOK. NO:37 SAMANDIRA,  
SANCAKTEPE/İSTANBUL**

and produced in the manufacturing plant

**ETK KABLO SANAYİ VE TİCARET A.Ş.**

**OSMANGAZİ MAH. MÜSTESNA SOK. NO:37 SAMANDIRA,  
SANCAKTEPE/İSTANBUL**

**EN 50575: 2014 + A1: 2016**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s) under system 1+ for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

**constancy of performance of the construction product .**

This certificate was first issued on 29.12.2025 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Ankara, 29.12.2025, Rev. 0



**PRODUCT DESCRIPTION:**

|                             |                    |
|-----------------------------|--------------------|
| Designation of cable family | CAT 6 / 6A U / FTP |
|-----------------------------|--------------------|

**RELEVANT CONSTRUCTIONAL INFORMATION:**

|                     |                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------|
| Conductor material  | Electrolytic solid copper conductor                                                                     |
| Rated diameter      | 7,1±0,5                                                                                                 |
| Insulation material | Foamed polyethylene clad with solid polyethylene                                                        |
| Cable core          | 4 number of Twisted Pair/Indv. Screen AlPet Tape / A tinned Copper Earthing Wire Between Screened Pairs |
| Sheath              | UV resistant, LSOH                                                                                      |

**ELECTRIC CABLES-EXTENDED APPLICATION OF TEST RESULTS FOR REACTION TO FIRE - EN 50576:**

|                                                                                               |
|-----------------------------------------------------------------------------------------------|
| Covered field                                                                                 |
| <input type="checkbox"/> U/UTP unscreened overall / unscreened twisted pair                   |
| <input type="checkbox"/> F/UTP screened overall / unscreened twisted pair                     |
| <input type="checkbox"/> SF/UTP metallic braid and screened overall / unscreened twisted pair |
| <input checked="" type="checkbox"/> U/FTP unscreened overall / screened twisted pair          |
| <input type="checkbox"/> F/FTP screened overall / screened twisted pair                       |
| <input type="checkbox"/> S/FTP metallic braid overall / screened twisted pair                 |
| <input type="checkbox"/> SF/FTP metallic braid and screened overall / screened twisted pair   |
| <input type="checkbox"/> Cable family including diameter ≤ 5mm                                |

**CABLE PARAMETER RANGE**

$\chi$  = Single data cable

**OUTER DIAMETER RANGE**

$D = 7,1 \text{ mm}$



This is the Annex to the Certificate of Constancy of Performance No. 3130-CPR-020.